

CM 100

Single Channel Electrocardiograph



- High resolution LCD screen 192 x 64, vivid waveform display
- 12 leads ECG simultaneous acquisition
- Built-in high-resolution thermal printer
- Built-in rechargeable Li-ion battery, AC/DC power supply
- Anti-defibrillation and Pace-maker detection
- Complete digital filtering, resisting baseline drift. Automatic baseline adjustment
- Automatic ECG measurement and interpretation
- Large patient data storage: 150ECGs
- Auto/manual work mode
- Well designed membrane keyboard
- Veterinary detection (option)



CM 100

Single Channel Electrocardiograph

Technical Specifications



Input Circuit	Defibrillator protection built-in
Lead	Standard 12 leads
Acquisition Mode	12-lead ECG simultaneously
A/D Converter	12 bits
Measurement range	$\pm 5\text{mVpp}$
Time Constant	$\geq 3.2\text{s}$
Frequency Response	0.05-150Hz
Calibrating Voltage	$1\text{mV} \pm 2\%$
Sensitivity	2.5, 5, 10, 20mm/mV
Input Impedance	$\geq 50\text{M}\Omega$
Input Circuit Current	$\leq 0.05\text{mA}$
Noise Level	$\leq 15\text{uVp-P}$
Anti Baseline Drift	Automatic
Filter	EMG Filter 25Hz/35Hz/45Hz/OFF DFT Filter 0.05/0.1/0.2/0.5Hz Lowpass Filter 150Hz/100Hz/70Hz AC Filter 50Hz/60Hz/OFF
CMRR	>100dB
Recording Mode	Auto: 1CH Manual: 1CH
Power Supply	AC:100V-150V / 220V-240V, 50/60Hz Built-in rechargeable Li-ion battery voltage=14.4V More than 2 hrs continuous work under batter supply
Recorder	Thermal Printer
Paper Style	Rolled or folded
Record Pater	50mm x 20m
Paper Speed	5mm/s, 10mm/s, 25mm/s, 50mm/s
Dimension	32mm x 28mm x 65mm
Weight	3kg (with battery)
Display	192 x 64 pixels LCD
External Input/Output	Input: $\geq 100\text{k}\Omega$: Sensitivity 10mm/V $\pm 5\%$ Output: $\leq 100\Omega$ Sensitivity 1V/V $\pm 5\%$
Communication Interface	Ethernet(option)



Compact, light weight and portable design



Automatic measurement report



High quality accessories

Shenzhen Comen Medical Instruments Co., Ltd.

Add: Floor 7, Block 5, 4th Industrial Park of Nanyou, Nanshan District, Shenzhen City 518052, China
Tel: +86-755-2640 8879 2641 9446 Fax: +86-755-2643 1232
Website: www.szcomen.com E-mail: info@szcomen.com